

AvediaStream g4190

The AvediaStream g4190 gateway streams live TV and Radio (news, sports, entertainment, educational) channels over your existing network. It distributes free to air TV content from one ASI source to an IP network.

Additional benefits of this TVgateway include:

- Easy Setup
- Hot swap module allows quick and non intrusive upgrade to existing installations
- Streams both SD and HD Channels simultaneously
- One ASI input per blade for free to air TV or radio channels
- Advanced PID filtering for fine-grained control over audio, subtitles and other channel metadata
- Embedded system for high reliability and low power consumption



g4190
Blade

Technical Specifications

Interfaces

One ASI input (75 ohm BNC input connector, 75 ohm BNC output connector for pass-through)
802.3 10/100BaseT Ethernet (RJ-45 chassis socket)
Serial RS232 Port for local administration (RJ-45 chassis socket)

Streaming

Up to 80Mbps output per blade or stream
Single/multiple program MPEG-2 transport streams (ISO/IEC 13818-1)
RTP
UDP
IP multicast
IP unicast
IGMP
Channel announcement using SAP/SDP

Administration Interface

Configurable DVB-C scanning
Stream specific channels from selected multiplex
Multicast/unicast address selection (automatic or manual)
Configure name, number or group membership per channel
Channel customisation using advanced filtering

- Create custom SPTS or MPTS streams containing elements from any channel on received multiplex
- Filters on PSI data, Program stream types, Audio Languages and PID number
- Unlimited number of PIDs filtered

Management

Fully integrated with all Exterity management tools
Network administration via HTTP web interface, SNMP & Telnet
Serial RS232 Admin Port
Telnet Control Interface (TCI)
Event logging via Syslog (RFC 3164) local and remote
Firmware upgrade via TFTP
Configuration backup/restore via TFTP

Chassis

C1

C3

C10

Resolution

SD

HD

ASI Input

Physical layer: ASI
Supported Standards: DVB-ASI, ATSC-ASI

System

CPU: MIPS 4Kc 492MHz
RAM: 64MB
Flash: 16MB (for firmware and configuration)
OS: Linux 2.6

Network

Linux IPv4 stack
DHCP or Static IP addressing
IEEE 802.3u 10/100Mbps MDIX Ethernet

Protocol

IP (RFC 791), UDP (RFC 768), TCP (RFC 793), ARP (RFC 826), DNS (RFC 1035), DHCP (RFC 2131), ICMP (RFC 792), IGMP v3 (RFC 3376), TFTP (RFC 1350), HTTP (RFC 2616), Telnet (RFC 318) Syslog (RFC 3164), NTP (RFC 1305), SAP (RFC 2974), SDP (RFC 4566), RTP (RFC 3550), RTSP (RFC 2362), SNMP (v1, v2c -RFC 1901)

Power

DC 24V: 12W Typical, 15W Maximum

Physical Format

Modular hot swap blade for Exterity chassis
AvediaStream c1101 providing 1 inputs
AvediaStream c1103 providing up to 3 inputs
AvediaStream c1110 providing up to 10 inputs

Dimensions

L: 275mm x W: 130mm x H: 40mm

Weight

0.5kg

Environment

Operating: 0 ...+40°C / +32 ... +104°F
Storage: -20 ...+70°C / -4 ... +158°F
Operating and storage Relative Humidity: 10-90% (non-condensing)

Regulatory

CE:
EN55022: 2006, EN61000: 2006, EN55024:2003
IEC 60950-1 1st Ed 2001, EN-60950-1: 2004

UL/CSA:

47CFR: 2008, ANSI C63-4: 2003
CSA 60950-1-03, 1st Ed. UL 60950-1, 1st Ed.

More Information on TVgateways

	g4130	g4150	g4155	g4170	g4190	g4210	g4215	g4230	g4235
DVB-C		✓	✓						
DVB-T	✓							✓	✓
DVB-T2								✓	✓
DVB-S						✓	✓		
DVB-S2						✓	✓		
ATSC/clear QAM				✓					
ASI					✓				
1 Tuner/CAM			✓				✓		✓
2 Tuners	✓	✓		✓		✓		✓	

United Kingdom Headquarters

t: +44 (0) 1383 828 250
f: +44 (0) 1383 824 905

South Europe Sales

t: +33 (1) 58 04 26 75
f: +33 (1) 58 04 23 00

United Kingdom Sales

t: +44 (0) 1383 828 250
f: +44 (0) 1383 824 905

Middle East Sales

t: +971 4 4204557
f: +971 4 3638302

North America Sales

t: +1 (404) 585 3520
f: +1 (404) 585 3524

w: www.exterity.com
e: info@exterity.com

